



## FAST RECOVERY RECTIFIER

# BY296 THRU BY299

VOLTAGE RANGE  
CURRENT


100 to 800 Volts  
2.0 Ampere

### FEATURES

- Fast Switching for high efficiency
- Low reverse leakage
- High forward surge current capability
- High Temperature soldering guaranteed:  
260°C / 10 second, 0.375" (9.5mm) lead length

### MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Polarity: Color band denotes cathode end
- Mounting Position: any
- Weight: 0.014 ounce, 0.3 gram



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	BY296	BY297	BY298	BY299	UNIT
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	100	200	400	800	Volts
Maximum RMS Voltage	$V_{RMS}$	70	140	280	560	Volts
Maximum DC Blocking Voltage	$V_{DC}$	100	200	400	800	Volts
Maximum Average Forward Rectified Current, 0.375" (9.5mm) lead length At $T_C = 50^\circ\text{C}$	$I_{(AV)}$	2.0				Amps
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	$I_{FSM}$	70				Amps
Maximum Instantaneous Forward Voltage @ 2.0A	$V_F$	1.3				Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage per element	$I_R$	$T_A = 25^\circ\text{C}$ 5.0				$\mu\text{A}$
		$T_A = 100^\circ\text{C}$ 200				
Maximum Reverse Recovery Time Test conditions $I_F = 0.5\text{A}$ , $I_R = 1.0\text{A}$ , $I_{RR} = 0.25\text{A}$	$t_{rr}$	500				nS
Typical Junction Capacitance (Measured at 1.0MHz and applied reverse voltage of 4.0V)	$C_J$	25				pF
Typical Thermal Resistance (Note 1)	$R_{\theta JA}$	40				$^\circ\text{C}/\text{W}$
Operating Junction Temperature Range	$T_J$	(-50 to +150)				$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	(-50to +150)				$^\circ\text{C}$

### Notes:

1. Thermal resistance from Junction to ambient at 0.375" (9.5mm) lead length mounted on PCB



# RATINGS AND CHARACTERISTIC CURVES BY296 THRU BY299

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE




FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC

